




At SWM International, we specialize in the extrusion of high-performance materials, including engineering-grade thermoplastics and fluoropolymers. Our profile extrusion line offers a unique range of products suitable for applications in a variety of harsh environments.



Coretec



*Rod, Pipe, Tube, and
Open Profile Extrusions*



SWM manufactures an extensive line of **Coretec™** profile extrusion products. Our high-end tubing, rods, pipes, and open-profile shapes are designed to meet aggressive requirements related to temperature, chemicals, moisture, and other extremes. We produce a range of stock items, as well as customized solutions, and we pride ourselves in our ability to offer unmatched products and services to demanding industries.

Coretec

www.swmintl.com

Regulatory Requirements

- FDA Compliant
- NSF Approvable
- ROHS Compliant
- UL Rated
- USP Class VI

Flexibility to Meet Varied Customer

Needs SWM recognizes the value of providing customized solutions to our partners. We build relationships with both our customers and our suppliers to ensure that we offer the best quality and service. We stay current on high-performance material issues to aid in product selection. We offer same-day shipments, drop shipments, and stocking agreements, as well as product customization per application. We strive to maintain high quality and achieve customer satisfaction with every order.



SWM International manufactures an extensive collection of fractional tubing, in multiple materials and colors.

Performance Requirements

- Abrasion Resistance
- Chemical Resistance
- Chemically Inert
- Excellent Clarity
- Low Coefficient of Friction
- High Dielectric Strength
- Dimensional Stability
- Electrical Properties
- Low Extractables
- Flame Resistance
- High Impact Strength
- High Mechanical Strength
- Low Moisture Absorption
- High Purity
- Steam Resistance
- Thermal Stability
- Excellent Weatherability

Engineering-Grade Thermoplastics

| Resin | Minimum Outside Diameter | Maximum Outside Diameter |
|------------------------------------|--------------------------|--------------------------|
| Acetal | 1/8" (0.3 cm) | 3" (8 cm) |
| PPO (NORYL® brand) | 1/8" (0.3 cm) | 6" (15 cm) |
| Polyetheretherketone (PEEK™ brand) | 1/16" (0.15 cm) | 6" (15 cm) |
| Polycarbonate (LEXAN® brand) | 1/8" (0.3 cm) | 12" (30 cm) |
| Polypropylene | 1/8" (0.3 cm) | 12.75" (32 cm) |
| Polysulfone | 1/8" (0.3 cm) | 10" (25 cm) |
| Polyphenylsulfone (RADEL®R brand) | 1/8" (0.3 cm) | 6" (15 cm) |
| Polyetherimide (ULTEM® brand) | 1/8" (0.3 cm) | 6" (15 cm) |



High performance PEEK Coretec pipes and tubes are available in a wide range of diameters and wall thicknesses.

Fluoropolymers

| Resin | Minimum Outside Diameter | Maximum Outside Diameter | Maximum Temperature |
|-------------------------------|--------------------------|--------------------------|---------------------|
| ECTFE (HALAR® brand) | 1/8" (0.3 cm) | 8" (20 cm) | 300°F (149°C) |
| ETFE (TEFZEL® brand) | 1/8" (0.3 cm) | 8" (20 cm) | 300°F (149°C) |
| FEP (TEFLON® brand) | 1/8" (0.3 cm) | 8" (20 cm) | 400°F (204°C) |
| PCTFE | 1/8" (0.3 cm) | 3" (8 cm) | 325°F (163°C) |
| PFA (TEFLON® brand) | 1/8" (0.3 cm) | 8" (20 cm) | 500°F (260°C) |
| PVDF (KYNAR® & SOLEF® brands) | 1/8" (0.3 cm) | 12.75" (32 cm) | 250°F (121°C) |



USA

308 Poplar Street • Richland, PA 17087-0678
717-866-7472 • Fax: 717-866-0301

www.swmintl.com • 800-521-6713

Coretec® is a trademark of SWM International.

Noryl®, Lexan®, & Ultem® are registered trademarks of SABIC Innovative Plastics Holding BV.

PEEK™ is a trademark of Victrex plc.

Radel® and Solef® are registered trademarks of Solvay Advanced Polymers, L.L.C. Halar® is a registered trademark of Ausimont USA, Inc.

Tefzel® and Teflon® are registered trademarks of E. I. du Pont de Nemours and Company used under license.

Kynar® is a registered trademark of Arkema or one of its affiliates.